Industrial Intercom



- Special keypad to be operated with work gloves. It is covered with silicone caps to protect it from dust and moisture.
- Cardioid dynamic microphone built into the cabinet to transmit from noisy environments.
- With its own 5 W amplifier and outputs to speakers to amplify the voice in noisy places.
- Built in metal cabinet resistant to intensive use.

- 10 mm diameter LEDs indicating the origin of the call.
- Terminal board connected to the built-in device installation.
- Independent audio volume control for transmission and reception.
- Capacity for 6, 12 and 18 internal numbers.
- Higher capacities on request.
- Painted with epoxy paint.

INTERCRON

• Compatible with our models I.C.10 and I.C.20 for installation in office areas.



BON

HORN SPEAKERS

0

- Round metal body with mounting bracket.
- Independence 8 Ohm.

0

•

Maximum power 25 Watts.

OPTIONAL:

Strobe light

 Flash lamp visible from a long distance.

4-inches acrylic optics.

It is activated when receiving a call and off when answering or in 30 seconds if no answer

OPTIONAL:

General call

0

With the addition of a module, you can call all devices at the same time, pressing only one button.

.

AUDIO PAGING SYSTEM

.

15

14

.

12

10

13

With one of the intercom buttons, you can communicate to a network of speakers and / or hornspeakers with built-in amplifier to locate people away from their work areas.

16

Industrial Intercom

